



KAM® E-IAS™
1.25" fixed insertion model

PER API 8.2,
ASTM D4177 AND ISO 3171

APPLICATIONS

- LACT units
- Truck loading, unloading
- Marine loading, unloading

MODELS

Fixed Insertion: 1.25" NPT or flange
 Flow through: 1 and 2" flanged spool
 Insertable: 2, 3 and 4" flanged seal housing
 2" MNPT flanged seal housing

Incorporating the same sampling principle as the time-tested KAM® IAS™, the all new KAM® E-IAS™ represents our first ever electric-drive automatic sampler. With multiple in-line installation options, the E-IAS™ is ideal for LACT and other custody transfer systems. The E-IAS™ is fully compliant with API Chapter 8.2, offering flow-proportional sampling without pneumatic or hydraulic drive requirements.

SPECIFICATIONS

Media:	Liquid hydrocarbons, including crude oil and condensate
Materials:	Wetted parts SS316, Peek Standard O-rings Viton
Bite size:	.5, 1 or 2 cc
Sample rate:	20 samples/minute max
Viscosity:	1-500 cSt
Pipe size:	1 – 36"
Max pressure:	285 psi
Temperature:	-40° to 350°F (-40° to 177°C)
Electrical	
Requirements:	120 VAC or 24 VDC PH 60 Hz 5.6 A -20 °C to +50 °C
Motor:	High-torque stepper motor

KAM CONTROLS is an ISO9001 Certified Company
www.KAM.com
 T: +1 713 784 0000
 F: +1 713 784 0001
 E: sales@KAM.com