

Meets API 8.2, ASTM D4177, ISO 3171, API 8.3 and ASTM 5854



**FLOW METER**  
Communicates flow data with Sampler Controller



**KAM<sup>®</sup> SC<sup>™</sup>**  
SAMPLER CONTROLLER  
Paces Sampler based on flow and volume data



**KAM<sup>®</sup> METERIZER**  
or **KAM<sup>®</sup> WEIGHT SCALE**  
Confirms sampling volume



**KAM<sup>®</sup> SR<sup>™</sup>**  
SAMPLE RECEIVERS  
3, 5, or 10 gallon

**KAM<sup>®</sup> IAS<sup>™</sup>**  
ISOKINETIC AUTOMATIC SAMPLER  
Takes samples and deposits them in the Sample Receiver (0.5 – 5 ml per bite)

The KAM<sup>®</sup> IAS<sup>™</sup> Isokinetic Automatic Sampler employs the simplest design in the industry and is designed to minimize down time and maintenance with convenient features such as fully insertable probes and standard seals and O-rings.

Include KAM<sup>®</sup> mixing solutions for API compliance, and the KAM<sup>®</sup> LRW<sup>™</sup> Low Range Watercut meter for real-time data.

KAM<sup>®</sup> SR<sup>™</sup> Sample Receivers prevent sample contamination with a custom lip seal and incorporate internal spray bars for fast mixing in the lab.

**SPECIFICATIONS: KAM<sup>®</sup> IAS<sup>™</sup>**

<b>Media:</b>	<b>Crude oil, refined products, chemicals, water and wastewater</b>
<b>Material:</b>	<b>316SS shaft, 304SS piston, teflon seal</b>
<b>Fluid temp:</b>	<b>-40° to 350°F (-40° to 177°C)</b>
<b>Power:</b>	<b>Air pneumatic</b>
<b>Sample size:</b>	<b>0.5 ml - 5 ml</b>
<b>Repeatability:</b>	<b>Exceeds API 8.2</b>
<b>Mounting:</b>	<b>Instertable/retractable with 2" MNPT* or 2", 3", or 4" flanged seal housing for main line 1.25" MNPT or flanged fixed insertion for lines up to 6" Flow Through 1" or 2" spool for fast loop</b>
<b>Pressure ratings:</b>	<b>ANSI 150, 300, 600, 900</b>
<b>Pipe size:</b>	<b>2" to 96"</b>

**SPECIFICATIONS: KAM<sup>®</sup> SR<sup>™</sup>**

<b>Pressure:</b>	<b>Design -130 psig</b>
<b>Material:</b>	<b>Stainless steel with viton lip seals</b>
<b>Inlet:</b>	<b>1/2" Male quick connect</b>
<b>Outlet:</b>	<b>3/4" Male quick connect</b>
<b>Sizes:</b>	<b>3, 5, 10, 15 gallon</b>

**SPECIFICATIONS: KAM<sup>®</sup> CSM<sup>™</sup>**

<b>Pump:</b>	<b>Gear pump - 4 GPM (16 LPM) or 9 GPM (34 LPM)</b>
<b>Motor:</b>	<b>Explosion proof 1/2 HP; 110/220 VAC, 50/60 Hz</b>
<b>Suction/discharge:</b>	<b>3/4" female quick disconnect / 1/2" female quick disconnect</b>
<b>Sample draw-off:</b>	<b>1/4" valve with tubing connection</b>

\* Seal Housing for 2" MNPT Models are Carbon Steel.

**FOR MORE INFORMATION ON KAM PRODUCTS**

**Phone:** +1 713-784-0000

**Fax:** +1 713-784-0001

**Email:** sales@kam.com

**www.KAM.com**

KAM CONTROLS, INC.

3939 Ann Arbor Drive

Houston, TX 77063 USA

KAM CONTROLS IS AN ISO 9001

CERTIFIED COMPANY

